

## Swing gate

### BU-SW024



#### MECHANICAL SWING GATES

It is designed to work with checkout posts. The gate can open in two directions, left or right. Opening direction can be changed at site by changing the socket of the bumper M10 bolt. The gate is not self re-tracking and is locked by a patented locker. It is made of steel coated with nickel chromium. To be used in closed places. Weight - 12 kg. Dimensions (Height\*Width): 1005\*800mm.

#### PRODUCT MAIN FEATURES

- ⊕ Universal checkout and partition swing gate
- ⊕ Mounted on pipes connecting low-partition posts
- ⊕ Designed to regulate customer flow in checkout zones
- ⊕ Bi-directional operation (left-right)
- ⊕ User-adjustable opening direction via bumper socket (M10 screw)

## AVAILABLE COLORS



BLACK

## TECHNICAL DATA

Model	BU-SW024
Gate type	Checkout / partition swing gate
Direction of travel	Bi-directional (left-right)
Opening	Manual; non-self-re-tracking
Locking	Locked by a patented locker
Dimensions (H x W)	1005 x 800 mm
Weight	12 kg
Material	Nickel-chromium coated steel
Application	Indoor use (closed places)
Mounting	Designed for checkout posts
Adjustment	Change of bumper socket (M10 bolt)

