



TURNSTILE GATES LOW - TRIPODS

The BO-DS112-SS turnstile is an elegant access control solution that can aesthetically fit into any room. The device is made of stainless steel and has an LED strip indicating whether or not access has been granted. You can set the gate to open unidirectionally or bidirectionally. The BO-DS112 turnstile is resistant to weather conditions, so it can be installed both inside and outside the building.

MAIN FEATURES

- ⊕ Long service life
- ⊕ High operational reliability
- ⊕ The device is characterized by quiet operation
- ⊕ Automatic lock after 5 seconds (can be changed) if the passenger does not pass through the gate
- ⊕ Anti-trailing: Only one person passes at a time
- ⊕ Automatic lowering of the arms in the event of a power cut
- ⊕ LED lamps (red × means no access; green → means open input)
- ⊕ Arm length can range from 500mm up to 650mm
- ⊕ The gate can work inside and outside the building



TECHNICAL DATA

Model	BO-DS112-SS
Material	Stainless steel 304
Dimensions	1200*230*980mm
Weight	50kg
Passage width	550mm (Arm length: 500mm)
Passage direction	Unidirectional or bidirectional
Power supply	AC 220V/110V, 50/60Hz
Operational voltage	24V DC
Power consumption	40W
Working temperature	-20°C up to 75°C
Humidity	0 ~ 95%
Working environment	Internal, external
Throughput	35-40 persons per minute
LED strip	Yes
Emergency mode	In case of power failure arms will be folded automatically
Communication	Dry contact, relay signal, RS485