



### SPEED GATES

BS-DS9000 is a sensory gate with a plexiglass wing with the option of extending the wing up to 1800mm high (by default it is 900mm high). The width of the passage may be from 550-900 mm, which meets the standards of passage for people on a wheelchair. It can work both in one and two directions.

### MAIN FEATURES

- ⊕ Long lifetime and high reliability
- ⊕ Low noise
- ⊕ Automatic lock function (if a passing person does not pass the gate within 5 seconds (can be adjusted), the arms will be blocked)
- ⊕ Passage will be opened automatically in case of power failure
- ⊕ Anti-burglar function - turnstile is defaultly closed, it can be opened after receiving a opening signal
- ⊕ Alarm function in case of an attempt to pass through the gate illegally (optional)
- ⊕ The mechanism will not be damaged if the arm meets resistance



## TECHNICAL DATA

Model	BS-DS9000
Material	Stainless steel, plexiglass
Gate module dimensions	1440*192*1000mm
Weight	75kg
Passage width	550-900mm
Passage direction	Unidirectional / Bidirectional
Arm height	900-1800mm
Power supply	AC220V/110V, 50/60Hz
Operational voltage	24V DC
Power consumption	40W
Working temperature	-20°C - 75°C
Humidity	95%
Working environment	External (IP65) / Internal
Throughput	40-45 people per minute
Emergency function	Passage will be opened automatically in case of power failure
Communication	Dry contact, relay signal, RS485

