



#### **AUTOMATIC SWING GATE**

BU-DS225GL-SS is an automatic swing gate with an attractive appearance and reliable operation. The arm is made of plexiglass. The passage width of 900 mm makes the gate suitable for disabled people in a wheelchair. Suitable for both indoor and outdoor installation. The gate can operate both unidirectionally and bidirectionally.

#### **MAIN FEATURES**

- ⊕ Long lifetime and high reliability
- ⊕ Low noise
- ⊕ Alarm function in case of an attempt to pass through the gate illegally
- ⊕ Only one person can pass through the gate in one cycle
- ⊕ Automatic lock function (if a passing person does not pass the gate within 5 seconds (can be adjusted), the arms will be blocked)
- ⊕ Anti-burglar function - turnstile is defaultly closed, it can be opened after receiving an opening signal
- ⊕ Passage will be opened automatically in case of power failure
- ⊕ Easy installation

## AVAILABLE COLORS

**SILVER****BLACK**

## TECHNICAL DATA

Model	BU-DS225GL-SS
Finish	Stainless steel
Arm material	Plexiglass
Dimensions	230*1015*1050mm
Weight	25kg
Passage width	≤900mm
Passage direction	Unidirectional / Bidirectional
Power supply	AC220V/110V, 50/60Hz
Voltage	24V DC
Power consumption	20W
Working temperature	-20 °C - 75 °C
Humidity	0 ~ 95%
Working environment	Internal / External
Throughput	35-40 people per minute
LED indicator	Yes
Emergency function	Passage will be opened automatically in case of power failure
Communication	Dry contact, relay signal, RS485

