



LOW HEIGHT TURNSTILE

BO-DZ403 is a turnstile made of brushed steel. The gate has many advanced functions, such as protection against dragging or opening passages in the event of a power failure. Suitable for indoor and interior installation.

PRODUCT MAIN FEATURES

- ⊕ Long service life and high reliability
- ⊕ Quiet operation
- ⊕ The device is equipped with an adjustable hydraulic motor
- ⊕ Automatic lock function (when a passing person does not pass through the gate for 5 seconds, the arms will block. You can set the time to pass through the gate yourself)
- ⊕ The passage will automatically open in the event of a power loss
- ⊕ It has an anti-trailing function - only one person will be able to pass through the gate during one opening

AVAILABLE COLORS




SILVER


TECHNICAL DATA

Model	BF-DZ403
Material	Brushed stainless steel 304
Dimensions	1406 * 1370 * 1050mm
Weight	80kg
Passage width	560mm
Passage direction	Single directional / Bi-directional
Power Supply	AC220V/110V, 50/60Hz
Operation Voltage	24V DC
Power consumption	40W
Operation Temperature	-15°C - 60°C
Operation Humidity	95%
Working Environment	Indoor /Outdoor (Shelter)
Flow Rate	35-40 people per minute
Emergency	Arms will open automatically
Communication	Dry contact, relay signal, RS485

Front view



Side view



View from the top

