



## Tripod

### BO-CRB100 Double

#### TURNSTILE GATES LOW - TRIPODS

The BO-CRB100 Double is a dual-module access control turnstile constructed from AISI 304 stainless steel with anodized, thermally treated aluminum arms, offering high durability, outdoor resistance and increased throughput in a compact design; the system provides adjustable bidirectional passage, memory mode, transition signaling and a bidirectional LED display, while in emergency situations (fire alarm) the arms automatically switch to free-rotation mode (NC) to allow fast and safe evacuation.

#### MAIN FEATURES

- ⊕ Dual configuration for increased throughput
- ⊕ AISI 304 stainless steel body, resistant to outdoor conditions
- ⊕ Anodized and thermally treated aluminum arms
- ⊕ Adjustable bidirectional passage
- ⊕ Transition signaling A→B and B→A (5VDC)
- ⊕ Adjustable transition time
- ⊕ Memory mode
- ⊕ Audible alarm
- ⊕ Standard bidirectional LED display
- ⊕ Emergency free-rotation mode (NC)
- ⊕ Low power consumption: 3.7W during passage / 4W standby
- ⊕ Suitable for indoor and outdoor installations



## TECHNICAL DATA

Model	BO-CRB100 Double
Body material	AISI 304 stainless steel
Arms material	Anodized and thermally treated aluminum
Passage Direction	Bidirectional, adjustable
Operation	Manual driving
Functions	Transition signals A→B / B→A (5VDC), adjustable time, memory mode, audible alarm
Emergency Mode	Free-rotation (NC) triggered by fire alarm
Power Supply	100–230 VAC, 47–60 Hz
Power Consumption	3.7W during passage / 4W in standby
Operating Temperature	-10°C to +70°C (optional heater: down to -30°C)
Passage Speed	Up to 26 people/min
Passage Width	450–500 mm
LED Display	Standard in both directions
Weight	~24 kg
Security Level	Deterrent
Areas of Use	Indoor and outdoor applications
Options (change the price)	Glass top cover, reader units, push-button, remote control, angled cover

