



Tripod

BO-CRB200

TURNSTILE GATES LOW - TRIPODS

The BO-CRB200 turnstile is a robust and modern access control solution built from outdoor-resistant AISI 304 stainless steel with anodized and thermally reinforced aluminum arms; it ensures high durability, smooth operation and full control over passage direction, offering adjustable passage timing, memory mode, A→B/B→A signaling and a standard bidirectional LED display, while in emergency scenarios (fire alarm) the arms automatically switch to free-rotation mode (NC) for fast and safe evacuation.

MAIN FEATURES

- ⊕ AISI 304 stainless steel body suitable for outdoor conditions
- ⊕ Anodized and thermally reinforced aluminum arms
- ⊕ Adjustable bidirectional passage
- ⊕ A→B and B→A transition signaling (5VDC)
- ⊕ Adjustable transition time and memory mode
- ⊕ Audible warning
- ⊕ Standard bidirectional LED display
- ⊕ Emergency free-rotation mode (NC)
- ⊕ Very low power consumption
- ⊕ Suitable for indoor and outdoor use



TECHNICAL DATA

Model	BO-CRB200
Body material	AISI 304 stainless steel
Arms material	Anodized and thermally treated aluminum
Passage Direction	Bidirectional, adjustable
Operation	Manual driving
Functions	Transition signals A→B / B→A (5VDC), adjustable time, memory mode, audible alarm
Emergency Mode	Free-rotation (NC) triggered by fire alarm
Power Supply	100–230 VAC, 47–60 Hz
Power Consumption	3.7W during passage / 4W in standby
Operating Temperature	-10°C to +70°C (optional heater: down to -30°C)
Passage Speed	Up to 26 people/min
Passage Width	450–500 mm
LED Display	Standard in both directions
Weight	~24 kg
Security Level	Deterrent
Areas of Use	Indoor and outdoor applications
Options (change the price)	Glass top cover, reader units, push-button, remote control, angled cover