



## Full height turnstile

### BW-BFI103 Double

#### FULL HEIGHT TURNSTILES - STADIUM

The BW-BFI103 Double is a dual high-security access control turnstile constructed from AISI 304 stainless steel, designed for environments requiring increased throughput and robust performance; it provides adjustable bidirectional passage, A→B/B→A signaling, adjustable transition time, memory mode, audible warning and a standard bidirectional LED display, while in emergency conditions (fire alarm) the arms automatically switch to free-rotation mode (NC). With a 56 cm passage width and a flow rate of up to 40 people per minute, it is suitable for heavy-traffic indoor and outdoor applications.

#### MAIN FEATURES

- ⊕ Dual-body design for increased flow capacity
- ⊕ AISI 304 stainless steel chassis
- ⊕ Adjustable bidirectional operation
- ⊕ A→B and B→A signaling (5VDC)
- ⊕ Adjustable passage time
- ⊕ Memory mode
- ⊕ Audible warning
- ⊕ Standard bidirectional LED display
- ⊕ Emergency free-rotation mode (NC)
- ⊕ High security level
- ⊕ Suitable for indoor and outdoor use

## AVAILABLE COLORS



SILVER



BLACK

## TECHNICAL DATA

Model	BW-BFI103 Double
Chassis Material	AISI 304 stainless steel
Passage Direction	Bidirectional, adjustable
Operation	Manual
Functions	A→B/B→A signaling (5VDC), adjustable timing, memory mode, audible warning
Emergency Mode	Free-rotation (NC) triggered by fire alarm
Power Supply	100–230 VAC, 47–60 Hz
Power Consumption	7.5W in transition / 8W on standby
Operating Temperature	-10°C to +70°C (optional heater: down to -30°C)
Passage Speed	Up to 40 people/min
Passage Width	56 cm
LED Display	Bidirectional, standard
Weight	~220 kg
Areas of Use	Indoor and outdoor
Options (change the price)	3- or 4-arm rotor, double-body version, pushbutton, remote control, passage LED spot lighting, counter, thermostat heater

