

Double swing gate

BU-DS205E-SS



AUTOMATIC SWING GATES

The BU-DS205E-SS double swing gate is a compact swing turnstile designed for entry and exit control in restricted indoor and outdoor areas. Made of brushed stainless steel, it provides a wide passage suitable for wheelchairs, strollers, bicycles, and users with large luggage. Commonly used in supermarkets and retail facilities, it ensures smooth operation, reliable access control, and automatic wing opening in case of power failure in compliance with fire safety requirements.

MAIN FEATURES

- ◊ Double swing gate for entry and exit control
- ◊ Wide passage for wheelchairs, bicycles, and large luggage
- ◊ 304 stainless steel construction
- ◊ Selectable single-direction or bi-directional operation
- ◊ Smooth and quiet operation for intensive use
- ◊ Automatic wing opening during power failure (fire safety compliant)
- ◊ Integration with access control systems and external devices

AVAILABLE COLORS

**SILVER****BLACK**

TECHNICAL DATA

Model	BU-DS205A
Framework Material	304 stainless steel
Arm Material	Plexiglas / stainless steel
Dimensions	168 × 1050 mm
Weight	25 kg / pc
Passage Width	600–900 mm (single passage)
Passing Direction	Single directional / Bi-directional
MCBF	5 million cycles
Power Supply	AC 220V / 110V, 50/60 Hz
Operating Voltage	24 V DC
Power Consumption	40 W
Operating Temperature	–15 °C to +60 °C
Operating Humidity	0–95% (no freeze)
Working Environment	Indoor / Outdoor
Flow Rate	Up to 30 people per minute
LED Indicator	No
Infrared Sensor	Optional
Emergency Mode	Automatic arm open when power off
Communication	Dry contact, relay signal, RS485